

Europäisches Patentamt

European Patent Office

Office européen des brevets



EP 0 777 347 A3 (11)

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3: 15.04.1998 Bulletin 1998/16 (51) Int. Cl.6: H04B 10/18, H04B 10/17

(43) Date of publication A2: 04.06.1997 Bulletin 1997/23

(21) Application number: 96117627.8

(22) Date of filing: 04.11.1996

(84) Designated Contracting States: FR GB

(30) Priority: 04.12.1995 JP 314976/95

(71) Applicant: Kokusai Denshin Denwa Kabushiki Kaisha Takya 163-03 (JP)

(72) Inventors:

· Akiba, Shiqeyuki, c/o Kokusai Denshin Denwa K.K. Tokyo 163-03 (JP)

· Yamamoto, Shu, c/o Kokusai Denshin Denwa K.K. Tokyo 163-03 (JP)

· Suzuki, Masatoshi, c/o Kokusai Denshin Denwa K.K. Tokyo 163-03 (JP)


· Edagawa, Noboru, c/o Kokusai Denshin Denwa K.K. Tokyo 163-03 (JP)

· Taga, Hidenori, c/o Kokusai Denshin Denwa K.K. Tokyo 163-03 (JP)

(74) Representative: Schaumburg, Thoenes, Thurn Patentanwälte Postfach 86 07 48 81634 München (DE)

Optical transmission system and optical repeater (54)

An optical transmission system comprises transmission optical fibers 14 connected between an optical transmission terminal 10 and an optical receiving terminal 12 via optical amplifying repeaters 16, and equalizing fiber 18 each connected in each equalizing interval. The equalizing fiber 18 is typically located at the terminal end of each equalizing interval. Each transmission optical fiber 14 is a dispersion-shifted fiber whose wavelength dispersion is substantially zero in a specific band, for example, 1.5 µm. The optical amplifying repeaters 16 include an optical amplifier, and a dispersion compensating optical element having wavelength dispersion characteristics that exhibit an inclination opposite from that of wavelength characteristics of wavelength dispersion of the transmission optical fiber 14 (more specifically, a minus inclination with respect to the wavelength). The dispersion compensating optical element compensates offset values of cumulative wavelength dispersion among different wavelengths. The dispersion compensating optical element can be made by a fiber grating technology.



Printed by Xerox (UK) Business Services 2,16.1/3.4



EUROPEAN SEARCH REPORT

Application Number EP 96 11 7627

DOCUMENTS CONSIDERED TO BE RELEVANT					
Category	Citation of document with income of relevant passa	lication, where appropriate,	Rele to ct	vant aim	CLASSIFICATION OF THE APPLICATION (Int.Ct.6)
X	TKACH R W ET AL: "T 20-GB/S CHANNELS OVE CONVENTIONAL SINGLE- IEEE PHOTONICS TECHN vol. 7, no. 11, 1 No pages 1369-1371, XPO * abstract * * page 1369, right-h	MODE FIBER" OLOGY LETTERS, Ovember 1995, OOO537980	1,2,4-7, 9,11-13, 15,16		H04B10/18 H04B10/17
Y	* figures 1,5 *		3,14		
Y	GRATINGS FOR COMPENS DISPERSION" OPTICS LETTERS, vol. 19, no. 17, 1 S	000461387 nand column, line 13 -	3,14		
X	P 0 684 709 A (AT & T CORP)		1,2,	4-6	TECHNICAL FIELDS SEARCHED (Int.CL6)
	* abstract * * column 3, line 13 * column 4, line 19 * column 5, line 6 * figures 1,2 *	- line 22 *			но48
A	EP 0 559 356 A (NORTHERN TELECOM LTD) * abstract * * column 1, line 37 - line 55 * * figure 1 *		1-17		
A	US 5 224 183 A (DUG * abstract * * column 4, line 30 * figure 2 *		8,10,17		
The present search report has been drawn up for all claims			1		
Place of search Date of completion of the search			'		Examener
1			Ribbe, A		
CATEGORY OF CITED OCCUMENTS T: theory or princ E: earlier patient of At particularly relevant if taken atone Y: particularly relevant if combined with another O: document of the document of the same category L: document often			I in the application		